PRODUCT SPECIFICATIONS

BC36 Circulating and BR36 Radiant Wood Burning Fireplaces



FIREBOX DIMENSIONS

Front opening width: 36" Front opening height: 21"

TECHNICAL INFORMATION

Flue Series (Std.): "SK8" Double Wall Flue Size: 8" Inner; 11" Outer Clearance to Chimney Pipe: 1-1/2" Firestop Framing: 14-1/2" x 14-1/2" Minimum Flue Height: 12' 6"

Maximum Flue Height: 90' Minimum Height with 2 Elbows: 14' 6" Minimum Height with 4 Elbows: 21'

Clearance to Fireplace: 1/2" to sides and back Minimum Hearth Extension Size: 16" x 48"

UL/ULC Design Certified

FIELD INSTALLED ACCESSORIES


Bi-fold Glass Doors: Brushed Brass, Black, Polished Brass, Pewter Fan Kit: FK12 (BC400/BC400i only)


EB1: Electrical Junction Box (BC400/BC400i only)


SCVS: Variable Speed Control for Fan (BC400/BC400i only)

Outside Air Kit: AK-MST


Terminations (Std.): "SK8" Series RLTSK8, RLTSK8L, PLTSK8, SLTSK8








*If elbows are offset to the back of the unit, chase depth will be 22⁵/8" (575mm).













LISTED