

Convert your wood burning fireplace to gas, for a new



standard of warmth, beauty, safety and convenience.

MODEL FUEL INPUT LOW FE (P.4.1-02) IDV33N / IDV36N NATURAL 31,000 / 34,250 BTU 20,900 / 24,000 BTU 57.4% / 58.4% IDV33LP / IDV36LP PROPANE 28,500 / 30,000 BTU 23,100 / 22,840 BTU 57.9% / 59.9%







- IDV33LP Direct Vent Fireplace Insert Propane, LOGF35 Split Fiber Oak Log Set – I33CVPW Clean View Kit – Pewter, I33SS1PW Surround for Clean View – Pewter, IDV33RL Refractory Brick Liner.
- IDV33LP Direct Vent Fireplace Insert Propane, LOGF35 Split Fiber Oak Log Set, I33CVCV Clean View Kit – Copper Vein, 33SS1CV Surround for Clean View – Copper Vein, IDV33RL Refractory Brick Liner.
- 3. IDV36N Direct Vent Insert Natural Gas, I36CVBL Clean View Kit – Black, LOGF36 Log Set, IDV36RLT Refractory Brick Liner – Traditional.

Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: The models IDV33 and IDV36 are certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2009, CSA 2.33-2009, CGA 2.17-M91.

*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.

MINIMUM FIREPLACE OPENING

	WIDTH	HEIGHT	DEPTH
IDV33	26 1/4"	21 3/8"	14 %"
IDV36	30 3/4"	25 5/8"	14 ³/8"

MINIMUM UNIT COVERAGE

IDV33	WIDTH	HEIGHT
IDV33 (Louvers) IDV33 (Clean View*)	34 ½" 32 ¾"	24 ³ / ₈ " 22 ³ / ₄ "
IDV36	WIDTH	HEIGHT

^{*}Back Frame Dimension of Clean View Kit

LOUVER KIT AND SURROUND SIZES

IDV33	WIDTH	HEIGHT
133LK (Louver Kit) 133S3426B (Surround) 133S4028B (Surround) 133S4430B (Surround) 133S4535B (Universal Surround)*	34 ½" 34 ½" 40" 44" 45"	24 3%" 27" 28 3%" 31 3%" 35"
IDV36	WIDTH	HEIGHT
136LK (Louver Kit) 136S3931B 136S4432B	39" 39" 44"	28 ³ / ₄ " 32 ³ / ₈ " 33 ¹ / ₈ "

 $[\]ensuremath{^*}$ Universal Surround can be cut to size for custom application.

CLEAN VIEW AND SURROUND SIZES

IDV33	WIDTH	HEIGHT
133CV (Clean View)	35 %"	24 ¼"
133SPF1	39 %"	29 ½"
133SSI	39 %"	26"
IDV36	WIDTH	HEIGHT
I36CV (Clean View)	40"	28 ½"
I36SS1	43 ½"	30 ¼"



Traditional Brick Liner RLT



Herringbone Brick Liner RLH

STANDARD FEATURES*

- Dual Burner with glowing embers
- Millivolt or IPI valve system allows operation during power failure with Hi-Low heat and flame control
- Matchless Piezo Ignition
- Decorative Ash Bed
- Log Set Fibre Split Oak*
- Ceramic Glass
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Bedroom and bed sitting room approval
- Mobile home, bedroom and bed sitting room approval

OPTIONAL FEATURES*

Clean View Kit – Black, Pewter, Copper Vein Surrounds for Clean View – Black, Copper Vein and Pewter

Surround Picture Frame for Clean View - Black

Louver Kit – Grills available in Black, Classic Series Black with Antique, Chrome, or Polished Brass accents

Surrounds for Louver Kit - Black

Wall Mount Thermostat – Standard On/Off or Programmable

Remote Control – On/Off, Thermostat, or Modulating Hi/Lo with Thermostat

Designer Doors – Arch or Straight Doors Brick Liner – Traditional or Herringbone

Child Safety Screen









2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

