



Easily turn your old, inefficient masonry fireplace into a cozy, cost-effective heat source with Direct Vent Insert Systems from Monessen. Featuring beautiful style, realistic flames and powerful heat output, these inserts provide everything you want in a fireplace while helping to lower fuel costs. And, with plenty of trim and surround options, it's easy to create the perfect look for your home.

Reveal ILDV40 with optional Black Texture Beveled Surround with hood shown on cover

REVEAL

DIRECT VENT INSERT SYSTEM

ILDV20, ILDV30 & ILDV40

Friends and family can enjoy the dancing flames through the large viewing area while staying warm, thanks to 39,000 BTUs of heating power. Standard features include Cottage Clay firebrick, a variable thermostat controlled forced air blower to help the fireplace operate at its most efficient, and a Natural Flame™ burner with a strikingly realistic ceramic fiber log set. Two styles and colors of designer facings give you plenty of options as you create the perfect look for your home.

Standard Features

- Clean face design
- Natural Flame[™] burner with ceramic fiber log set
- 3" intake and 3" exhaust vent pipe connectors for chimney flex liners
- Thermostat blower (160 cfm) standard
- 18" flex line with On/Off shut-off valve
- ON/OFF shut-off valve with easy access panel conveniently located on side of the firebox





Cottage Clay firebrick

Optional Accessories — Surrounds

for Reveal Direct Vent Insert Systems



Colonial surround in Iron Age with filigree option



Beveled surround in Black Texture with hood option



Beveled surround in Black Texture with filigree option



Beveled surround in Black Texture with louver option

Also available in Iron Age



ACCENT DIRECT VENT INSERT SYSTEM IDV380

The Accent Direct Vent Insert System features standard Black filigree trim and Cottage Clay firebrick to create a stylish, custom look. The larger, 382-square inch viewing area provides ambience that will light up the room. And, with heating power of up to 30,500 BTUs, you'll be sure to stay warm and comfortable. To make this fireplace insert truly your own, choose from a variety of optional accessories for the perfect look.

Standard Features

- Seven piece ceramic fiber logs featuring a patented Natural Flame™ burner with random dancing flames and large ember bed
- Millivolt with on/off switch and variable flame height control in natural gas or propane gas
- Black filigree panels
- Natural or propane field convertible
- Flexible connector with On/Off shut off valve included
- Consumer friendly deluxe control panel with on/off switch
- Thermostat controlled blower



Cottage Clay firebrick



Optional Accessories — Trim and Surrounds

for Accent Direct Vent Insert System













I380SMBL Clean Face Surround

Cabinet doors and door frames available in black

DIRECT VENT INSERTS

Dimensions Chart

Model #	ILDV20	ILDV30	ILDV40
BTU	13,000 - 20,000 NG / 16,000 - 20,000 LP	20,500 - 30,000 NG / 23,000 - 30,000 LP	27,000 - 39,000 NG / 30,000 - 38,000 LP
FE Ratings (Cdn. Fireplace Efficiency	65% NG / 73.9% LP	71.9% NG / 83.7% LP	70.8% NG / 79.8% LP
Dimensions (Actual)	30 ¼"W x 17 %"H x 15 ½6"D	34 %"W x 20 ¾"H x 17 %"D	37 1/16"W x 23 3/8"H x 18 3/8"D
Fireplace Opening Dimensions	22 ½"W (Front Width) x 18"H x 14"D x 15 ¼ (Rear Width)	28"W (Front Width) x 21"H x 16"D x 18" (Rear Width)	31"W (Front Width) x 23 ½"H x 16 ½"D x 23" (Rear Width)
Viewing Area	280 sq. in.	409 sq. in.	512 sq. in.
Design Certified	CSA	CSA	CSA

Model #	IDV380
BTU	20,500 - 30,500 (NG) 22,000 - 28,000 (LP)
FE Ratings (Cdn. Fireplace Efficiency	69.6% NG / 66.2% LP
Dimensions (Actual)	28"W x 21"H x 16"D
Fireplace Opening Dimensions	28"W x 21"H
Viewing Area	382 sq. in.
Design Certified	CSA

Additional Accessories







See our Ambient Technologies® catalog for complete line of remotes and thermostats.



A Brand of Monessen Hearth Systems Co. 149 Cleveland Drive, Paris, Kentucky 40361 www.monessenhearth.com





















To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2011 Monessen Hearth Systems Co. 10828-0111



For more information about MHSC and Monessen efficient and environmentally friendly products, please visit www.monessenhearth.com Ver 5. MON8408